




Series  
1950

# Explosion-proof Differential Pressure Switches

Compact, Low Cost, Explosion-proof and Weatherproof



## SPECIFICATIONS

**Service:** Air and non-combustible, compatible gases.  
**Wetted Materials:** Consult factory.  
**Temperature Limits:** -40 to 140°F (-40 to 60°C); 0 to 140°F (-17.8 to 60°C) for 1950P-8, 15, 25, and 50. -30 to 130°F (-34.4 to 54.4°C) for 1950-02.  
**Pressure Limits:** Continuous: 1950's - 45 in w.c. (0.11 bar); 1950P's - 35 psi (2.41 bar); 1950P-50 only - 70 psi (4.83 bar). Surge: 1950's - 10 psi (0.69 bar), 1950P's - 50 psi (3.45 bar), 1950P-50 only - 90 psi (6.21 bar).  
**Enclosure Rating:** NEMA 3 (IP54), NEMA 7 & 9.  
**Switch Type:** Single-pole double-throw (SPDT).  
**Electrical Rating:** 15 A @ 125, 250, 480 VAC, 60 Hz. Resistive 1/8 HP @ 125 VAC, 1/4 HP @ 250 VAC, 60 Hz.  
**Electrical Connections:** 3 screw type, common, normally open and normally closed.  
**Process Connections:** 1/8" female NPT.  
**Mounting Orientation:** Diaphragm in vertical position. Consult factory for other position orientations.  
**Set Point Adjustment:** Screw type on top of housing.  
**Weight:** 3.25 lb (1.5 kg); 1950-02 model, 4.4 lb (2 kg).  
**Agency Approvals:** CE, UL, CSA, FM.

**Model 1950 Explosion-Proof Differential Pressure Switch** combines the best features of the popular Dwyer® Series 1900 Pressure Switch with an integral explosion-proof and weatherproof housing, making it an exceptional value for either application. It is CE, UL and CSA listed, FM approved for use in Class I, Div 1, Groups C and D, Class II Groups E, F, and G and Class III hazardous atmospheres (NEMA 7 & 9), Raintight NEMA 3 (IP54). Weatherproof features include a drain plug and O-ring seal in cover. Electrical connections are easily made by removing front cover. For convenience the set point adjustment screw is located on the outside of the housing. Twelve models offer set points from .03 to 20 in w.c. (7.5 to 5 kPa) and from .5 to 50 psi (0.035 to 3.5 bar). The unit is very light and compact – about half the weight and bulk of other explosion-proof or weather-proof switches with separate enclosures.

### Series 1950 Switches - Operating Ranges and Dead Bands

Model	Range, Inches W.C.	Approximate Dead Band at		Price
		Min. Set Point	Max. Set Point	
1950-02-2S	.03 to .10	.025	.05	\$188.75
1950-00-2F	.07 to .15	.04	.05	130.00
1950-0-2F	.15 to .50	.10	.15	130.00
1950-1-2F	.4 to 1.6	.15	.20	130.00
1950-5-2F	1.4 to 5.5	.30	.40	130.00
1950-10-2F	3 to 11	.40	.50	130.00
1950-20-2F	4 to 20	.40	.60	130.00

Model*	Range, PSID	Approximate Dead Band at		Price
		Min. Set Point	Max. Set Point	
1950P-2-2F	0.5 to 2	.3	.3	\$151.00
1950P-8-2F	1.5 to 8	1.0	1.0	151.00
1950P-15-2F	3 to 15	.9	.9	151.00
1950P-25-2F	4 to 25	.7	.7	151.00
1950P-50-2F	15 to 50	1.0	1.5	151.00


**CAUTION:** For use only with air or compatible gases. Applications with hazardous atmospheres and a single positive pressure may require special venting. \*P=PSID range models



Series  
1950G

# Explosion-proof Differential Pressure Switch

Explosion-proof, Weatherproof, Compatible with Natural Gases



**The Model 1950G Explosion-Proof Switch** combines the best features of the popular Dwyer® Series 1950 Pressure Switch with the benefit of natural gas compatibility. Units are rain-tight for outdoor installations, and are UL listed for use in Class I, Groups A, B, C, & D; Class II, Groups E, F, & G and Class III atmospheres, Directive 94/9/EC (ATEX) Compliant for CE II 2G Exd IIB + H<sub>2</sub> T6, CSA & FM approved for Class I, Div 1, Groups B, C, D; Class II, Div 1, Groups E, F, G and Class III atmospheres IECEx Exd IIB + H<sub>2</sub> T6 (-40°C < Ta < +60°C). The 1950G is very compact, about half the weight and bulk of equivalent conventional explosion-proof switches. Easy access to the SPDT relay and power supply terminals is provided by removing the top plate of the aluminum housing. A supply voltage of 24 VDC, 120 or 240 VAC is required. A captive screw allows the cover to swing aside while remaining attached to the unit. Adjustment to the set point of the switch can be made without disassembly of the housing.

## SPECIFICATIONS

**Service:** Air and compatible combustible gases.  
**Wetted Materials:** Contact factory.  
**Temperature Limits:** 0 to 140°F (-17 to 60°C).  
**Note:** Set point drift may occur with ambient temperature changes.  
**Pressure Limits:** 45 in w.c. (11.2 kPa) continuous; 10 psig (68.95 kPa) surge.  
**Enclosure Rating:** NEMA 3 (IP54), NEMA 7 & 9.  
**Switch Type:** 1 Form C relay (SPDT).  
**Electrical Rating:** 10A, 120/240 VAC, 28 VDC. Resistive 50 mA, 125 VDC.

**Power Requirements:** 24 VDC ±10%. 120 or 240 VAC ±10% optional.  
**Electrical Connections:** Internal terminal block.  
**Process Connections:** 1/8" female NPT.  
**Mounting Orientation:** Diaphragm in vertical position. Consult factory for other position orientations.  
**Set Point Adjustment:** Screw type on top of housing.  
**Weight:** 2 lb, 15.7 oz (1.35 kg).  
**Agency Approvals:** CE, UL, CSA, FM, ATEX, IECEx.

Series 1950G-XX-B-24-NA	.....	\$198.00
Series 1950G-XX-B-24, ATEX	.....	279.50
Series 1950G-XX-B-240-NA, 240 VAC	.....	231.00
Series 1950G-XX-B-120-NA, 120 VAC	.....	198.00

UL, CSA, FM Model	ATEX Model	Range, Inches W.C.	Approximate Dead Band at	
			Min. Set Point	Max. Set Point
1950G-00-B-24-NA	1950G-00-B-24	.07 to .15	.04	.06
1950G-0-B-24-NA	1950G-0-B-24	.15 to .50	.06	.11
1950G-1-B-24-NA	1950G-1-B-24	.4 to 1.6	.11	.29
1950G-5-B-24-NA	1950G-5-B-24	1.4 to 5.5	.4	.9
1950G-10-B-24-NA	1950G-10-B-24	3 to 11	.9	1.8
1950G-20-B-24-NA	1950G-20-B-24	4 to 20	1.2	3.0